



## Sun Ray Panel Heater with Timer

ATC Sun Ray Panel Heaters are modern in design and are supplied with a wall mounting bracket for ease of installation.

Ideal for the home, office or shop, the Sun Ray Panel Heater range is available from 500W to 2000W and comes with a built in analogue 24 Hour time clock for accurate time control and energy saving.

## PRODUCT FEATURES • Wall Mounting (complete with bracket) • Three Models available (500/1000W) (750/1500W) (1000/2000W) • High Quality Aluminium Element • 24 Hour/ Weekly Timer • Neon On/Off Switch • Thermal Safety Cut Out • Protection IP20 • Colour White • Fitted with 1.5m Mains Cable APPROVALS (E) Intertek RoHS

## **TECHNICAL DATA**

| Kellihers Code     | 4030069                                     | 4030070                                     | 4030071                                     |
|--------------------|---|---|---|
| Description        | Panel heater wall mounted C/W 24 Hour Timer | Panel heater wall mounted C/W 24 Hour Timer | Panel heater wall mounted C/W 24 Hour Timer |
| Power (W)          | 500W/1000W (2 settings)                     | 750W/1500W (2 settings)                     | 1000W/2000W (2 settings)                    |
| Voltage (V)        | 220-240V                                    | 220-240V                                    | 220-240V                                    |
| Frequency (Hz)     | 50-60Hz                                     | 50-60Hz                                     | 50-60Hz                                     |
| Element            | High Quality Aluminium                      | High Quality Aluminium                      | High Quality Aluminium                      |
| Thermostat         | Adjustable                                  | Adjustable                                  | Adjustable                                  |
| Safety Cut-out     | 75°C  | 85°C  | 90°C  |
| Dimensions (LxDxH) | 576 x 106 x 440mm                           | 732 x 106 x 440mm                           | 940 x 106 x 440mm                           |
| Weight             | 5.17 KG                                     | 6.35 KG                                     | 8.15 KG                                     |
| IP Protection      | IP20  | IP20  | IP20  |
| Colour             | White                                       | White                                       | White                                       |
| Approvals          | CE, Intertek GS, RoHs                       | CE, Intertek GS, RoHs                       | CE, Intertek GS, RoHs                       |

