



Insulated enclosures Surface mounting

Fix-o-Rail Junior

IP40



Approvals / Marking



Standards

BS EN 60439-3

Applications



For new buildings, replacing old units and adding add-on devices.

Features

- High resistance material
- Modern design
- Compact construction
- High protection degree IP40
- Total insulation □
- Total security
- Transparent cover allowing visibility of devices
- For all modular equipment
- Available in 4 and 8 modules
- Colour: RAL 7035
- ABS for the base
Flame resistance: self extinguishing material, resist the 650 °C
- Polycarbonate for the lid
Flame resistance: self extinguishing material, resist the 960 °C



Dimensions ● pg F.52

Fix-o-Rail Junior

H x W x D (mm)	Equipment	No. of modules	Ref. No.	Pack.
170 x 90 x 100 Max. depth of the devices: 70 mm Entries: 2 x PG29, 4 x PG21	Earth terminal: connection 5 x 16 mm ² Neutral terminal: connection 5 x 16 mm ²	4	610344	1/15
170 x 175 x 120 Max. depth of the devices: 92.5 mm Entries: 2 x PG21, 4 x PG16	Earth terminal: connection 6 x 10 + 2 x 16 mm ² Neutral terminal: connection 6 x 10 + 2 x 16 mm ²	8	610345	1/8

Accessories

	Earth/neutral terminals For Junior 4 modules <table border="1"> <tr> <td>610141</td> <td>2</td> </tr> </table> Connection range 5 x 16 mm ²	610141	2	Sealing bracket <table border="1"> <tr> <td>610140</td> <td>2</td> </tr> </table>	610140	2				
	610141	2								
610140	2									
Earth/neutral terminals For Junior 8 modules <table border="1"> <tr> <td>610186</td> <td>4</td> </tr> </table> Earth connection range 6 x 10 mm ² + 2 x 16 mm ² <table border="1"> <tr> <td>610187</td> <td>4</td> </tr> </table> Neutral connection range 6 x 10 mm ² + 2 x 16 mm ²	610186	4	610187	4	Blank plate 4 modules <table border="1"> <tr> <td>610142</td> <td>4</td> </tr> </table> <table border="1"> <tr> <td>610484</td> <td>500</td> </tr> </table> length: 72 mm cut out width : 45 mm can be cut into 9 mm length RAL 7035	610142	4	610484	500	
610186	4									
610187	4									
610142	4									
610484	500									
Grommets <table border="1"> <tr> <td>610130</td> <td>25</td> </tr> </table> PG16 <table border="1"> <tr> <td>610132</td> <td>25</td> </tr> </table> PG21 <table border="1"> <tr> <td>610133</td> <td>25</td> </tr> </table> PG29	610130	25	610132	25	610133	25				
610130	25									
610132	25									
610133	25									