GU3220WSS

Ultimate Flat plate - switched socket - 2 gangs - stainless steel



Main

Range	Ultimate
Device application	Power supply
Aesthetic name	Flat plate
Product or component type	Switched socket
Rated current	13 A 230 V AC 50 Hz
Fixing mode	By screws M3.5 30 mm
Colour tint	Stainless steel

Complementary

Device presentation	Complete product	
Outlet poles configuration	1P	_
Outlet standard description	3 pins	_
Outlet standard	British	
Actuator	Rocker	
Number of gangs	2 gangs	
Earth circuit	Standard earth	
Pilot light	Without neon indicator	
Device mounting	Wall mounted	
Connections - terminals	Screw terminal	
Material	Stainless steel	
Quantity per set	Set of 1	
Height	88 mm	
Width	148 mm	
Depth	30 mm	
Socket number	2	
Mounting mode	Horizontal	_

Environment

IP degree of protection	IP20	
standards	BS	

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1639 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months	