

GU6212LSS

Ultimate Flat Plate dimmer switch 100W/VA, 1gang,
2way, LED, st.steel



Main

Range of product	Ultimate
Range	Ultimate
Aesthetic name	Flat plate
Product or component type	Dimmer
Device application	Control
Load type	230 V AC halogen lamp 230 V AC halogen lamp Incandescent lamp 100 W
Colour tint	Stainless steel
Quantity per set	Set of 1

Complementary

Switch function	2-way
Device mounting	Wall mounted
Dimmer application	Inductive load Resistive load
[Ue] rated operational voltage	230 V AC 50 Hz
Number of gangs	1 gang
Connections - terminals	Screw terminals
Height	88 mm
Width	88 mm
Depth	25 mm

Environment

standards	BS EN 60669-2-1
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.