



Main

| | |
|---------------------------|----------------------------------|
| Range | Lisse |
| Aesthetic name | White moulded |
| Product or component type | Switched socket with USB charger |
| Device presentation | Complete product |
| Outlet standard | British |
| Colour tint | Matt white |
| Earth circuit | Standard earth |
| Quantity per set | Set of 1 |
| Type of packing | Bag |

Complementary

| | |
|----------------------------|-------------------------|
| Switch function | 1-pole |
| Rated current | 13 A, 250 V AC 50 Hz |
| Integrated connection type | 2 USB port 5 V DC 2.1 A |
| Actuator | Rocker |
| Number of gangs | 2 gangs |
| Pilot light | Without LED |
| Fixing mode | By screws |
| Connections - terminals | Screw terminals |
| Material | Urea (carbamide) |
| Type of installation | Indoor |
| Depth | 31 mm |
| Width | 148.5 mm |
| Height | 87 mm |
| Product weight | 0.197 kg |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|-------------------------|----------------------|
| Standards | BS 1363-2 BS 5733 |
| IP degree of protection | IP20 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1642 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |