# Product datasheet Characteristics

# **GGBL5010**

Lisse - Fuse connection unit - 1 gang - 13 A - white moulded



#### Main

Aesthetic name White moulded  Product or component type Fuse connection unit  Device presentation Complete product  Colour tint White moulded cover plate	Range	Lisse	
Device presentation Complete product	Aesthetic name	White moulded	
	Product or component type	Fuse connection unit	
Colour tint White moulded cover plate	Device presentation	Complete product	
	Colour tint	White moulded cover plate	
Quantity per set Set of 10	Quantity per set	Set of 10	

### Complementary

· · · · · · · · · · · · · · · · · ·		C
Pilot light	Without LED	
Actuator	Rocker	
Number of gangs	1 gang	9
Material	Urea (carbamide)	
Device mounting	Wall mounted	-
Fixing mode	By screws	*
Rated current	13 A, 250 V AC	<u>.</u>
Connections - terminals	Screw terminals	
Type of packing	Carton	
Width	87 mm	
Height	87 mm	- 0
Depth	28 mm	
Product weight	0.101 kg	9.00
		c

#### Environment

Standards	BS 1363
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1642 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	