

# YY KONTROL KABLOSU

## YY CONTROL CABLE

PVC İZOLELİ VE KILIFLI, ÇOK TELLİ KONTROL KABLOSU  
PVC INSULATED AND SHEATHED, FLEXIBLE CONTROL CABLES

STANDARTLAR

STANDARDS

GEN TO BS EN  
50525-2-11  
VDE0250

SERTİFİKALAR  
CERTIFICATES

CE



### TEKNİK VERİLER / TECHNICAL DATA

### Cu/PVC/PVC

Nominal Kesit mm <sup>2</sup> Nominal Cross Section mm <sup>2</sup>	Yaklaşık Dış Çap mm Overall Diameter mm approximately	Yaklaşık Net Ağırlık kg/km Net Weight kg/km approximately	İletken Direnci Max. ohm/km(20°C) Conductor DC Resistance at 20°C max. ohm/km	Akım Taşıma Kapasitesi Current Carrying Capacity in Havada (A) Air (A)
<b>YSLY (300/500 V)</b>				
2x2,5	7,6	99	7,98	25
3x2,5	8,3	127	7,98	25
4x2,5	9,0	158	7,98	20
5x2,5	10,3	203	7,98	19,5
6x2,5	11,4	248	7,98	19,5
7x2,5	11,4	263	7,98	16,3
8x2,5	13,5	342	7,98	16,3
10x2,5	16,3	471	7,98	13,8
12x2,5	15,8	481	7,98	13,1
14x2,5	16,5	541	7,98	12,5
16x2,5	17,4	607	7,98	12,5
18x2,5	18,3	677	7,98	12,5
19x2,5	18,3	692	7,98	11,3
24x2,5	21,4	914	7,98	10,0
25x2,5	21,4	929	7,98	10,0
30x2,5	24,4	1173	7,98	9,40
36x2,5	25,2	1310	7,98	9,40
3x4	10,4	203	4,95	34
4x4	11,4	254	4,95	34
5x4	12,5	310	4,95	34
7x4	13,8	400	4,95	-
12x4	21,7	860	4,95	-
2x6	11,2	224	3,30	51
3x6	11,7	248	3,30	43
4x6	13,1	354	3,30	43
5x6	14,9	451	3,30	43
6x6	16,2	540	3,30	43
7x6	16,2	577	3,30	-
12x6	24,9	1194	3,30	-
3x10	15,5	474	1,91	59
4x10	17,0	594	1,91	60
5x10	18,7	729	1,91	-
7x10	20,4	934	1,91	-
3x16	17,9	683	1,21	79
4x16	19,7	864	1,21	80
5x16	21,6	1057	1,21	80
5x25	26,9	1609	0,780	101
4x25	25,1	1344	0,780	101
3x35	25,0	1395	0,554	129
4x35	27,4	1762	0,554	126
5x35	30,0	2135	0,554	126