



NEW YORK

IP65 PBT floods for 70W, 150W, 250W and 400W HID lamps



NEW YORK 250W - 400W ASYMMETRIC

NEW YORK 150W SYMMETRIC

NEW YORK 70W SYMMETRIC



APPLICATIONS

- Salt-laden environments and coastal areas, including:
 - Building signage illumination
 - Perimeter and security lighting
 - General amenity use

CONSTRUCTION

- HQI 70W, 150W, 250W and 400W
- SON 250W and 400W
- Supplied with European brand lamp
- 70W/150W symmetric distribution
- 250W/400W asymmetric distribution

TECHNICAL DETAILS

- Polybutylene therephthalate (PBT) body for salt and pollution resistance
- Black self-colour finish
- Stainless steel mounting bracket
- One-piece toughened glass cover on PBT hinges
- 3 body sizes with weights as follows:

WEIGHT & WINDAGE

Small body, 70W HQI
Weight 3.75kg, Windage 0.07m²

Medium body, 150W HQI
Weight 6.75kg, Windage 0.13m²

Large body,
Weight 250W SON & HQI 9.00kg
Weight 400W HQI 10.00kg
Weight 400W SON 11.20kg
Windage 0.19m²

OPTIONS

PHOTO-CELL Dusk/dawn photo-cell available. Suffix PEC

ORDER CODE	DESCRIPTION
NNY70HQI-DE/740	NEW YORK 70W MH PBT FLOOD + 740 LAMP
NNY150HQI-DE/740	NEW YORK 150W MH PBT FD.LIGHT + 740 LAMP
NNY250SON-T/220	NEW YORK 250W SON PBT FLOOD + 220 LAMP
NNY400SON-T/220	NEW YORK 400W SON PBT FLOOD + 220 LAMP
NNY250HQI-T/740	NEW YORK 250W MH PBT FLOOD + 740 LAMP
NNY400HQI-T/740	NEW YORK 400W MH PBT FLOOD + 740 LAMP
SPARES	
NNY/BRKT/250-400/3.5MM	NEW YORK MOUNTING BRACKET 250-400W

