



OREGON T5

A high performance fluorescent fitting with many sensor options



FLUORESCENT

APPLICATIONS

- Industry and warehouses
- Mounting heights 5+m

CONSTRUCTION

- Steel body, white textured paint finish
- Miro 4 reflectors for efficiency

TECHNICAL DETAILS

- For T5 54W and 80W, 3 and 4 lamps
- Supplied excluding lamps
- Leading brand ENEC control gear
- 1 lamp per reflector. LOR .93

OPTIONS

EMERGENCY Maintained 3 hours available. Add suffix M3.

DIMMING Add suffix DA, SD or CF.

SENSORS

- PIR occupancy sensing. Add suffix PIR
- PIR occupancy sensing and dim-to-10%. Add suffix CF/PIR
- PIR occupancy sensing and dimming. Add suffix PIRD
- Maintained light level only. Add suffix MLL

MODULAR WIRING. Available with panel-mount male connector fitted. Add suffix M02 (4-pole) or M05 (6-pole) as required.

HIGH-RACK REFLECTOR Add suffix HR.

ATTACHMENTS Polycarbonate covers and wire guards available. Enquire for details.

ORDER CODE	DESCRIPTION
NOR354/T5	OREGON 3X54WT5
NOR454/T5	OREGON 4X54WT5
NOR380/T5	OREGON 3X80WT5
NOR480/T5	OREGON 4X80WT5

