

TENNESSEE 2D

IP65 circular decorative cast aluminium bulkheads for 2D lamps.



Available with micro-wave occupancy sensor fitted to gear tray



APPLICATIONS

- Exterior walkways and stairs
- Building perimeters

SPECIFICATION

- 2 wattages available:
 - 28W with cold-start HF gear, not suitable for frequent switching (eg with a sensor)
 - 38W with warm-start ENEC standard HF control gear
- Supplied with colour 840 lamp

CONSTRUCTION

- Die-cast aluminium base and bezel
- Grey powder coated textured finish
- Polycarbonate opal diffuser
- Steel gear tray

OPTIONS

- **Emergency.** Maintained 3 hours available on 28W & 38W versions using Mackwell module. Suffix M3
- **Dimming.** Dim-to-10% (corridor function) available. Suffix CF.

- **Sensors.** Available with micro-wave occupancy sensor fitted to gear tray and warm-start gear. Suffix MW. Even with warm-start gear frequent switching will shorten 2D lamp life. Consider using the LED version. If considering the use of multiple MW sensors in the same circuit seek our advice first.
- **Vandal resistant.** For vandal resistant screws, add suffix VR. Vandal resistant screws are also available as spares, as listed below.

ORDER CODE	DESCRIPTION
NTN28/2D/HF/840	TENNESSEE 28W2D HF IP65 ALU BHEAD +840 LAMP
NTN28/2D/HF/M3/840	TENNESSEE 28W2D HF IP65 ALU BHEAD M3 +840 LAMP
NTN28/2D/HF/MW/840	TENNESSEE 28W2D HF IP65 ALU BHEAD MW +840 LAMP
NTN28/2D/HF/MW/M3/840	TENNESSEE 28W2D HF IP65 ALU BHEAD MW + M3 +840 LAMP
NTN38/2D/HF/840	TENNESSEE 38W2D HF IP65 ALU BHEAD +840 LAMP
NTN38/2D/HF/M3/840	TENNESSEE 38W2D HF IP65 ALU BHEAD M3 +840 LAMP
NTN38/2D/HF/MW/840	TENNESSEE 38W2D HF IP65 ALU BHEAD MW +840 LAMP
NTN38/2D/HF/MW/M3/840	TENNESSEE 38W2D HF IP65 ALU BHEAD MW +M3 +840 LAMP

SPARES

ORDER CODE	DESCRIPTION
NTN/TPSCREWS	TENNESSEE TAMPER PROOF SCREWS PACK OF 4 + TOOL

