



ABLED/3NM

Beacon LED Emergency Adjustable Downlight Non-Maintained 5W



Features

LED Non-Maintained adjustable die-cast aluminium downlight.

3 hour emergency output.

Power and green charge LED are discreetly incorporated within the head.

120° beam angle.

General Information

| | |
|--------------------------------|----------|
| Lamp Type | LED |
| Colour / Finish | White |
| Emergency | Yes |
| Self Test | Yes |
| IP Rating | IP20 |
| Class Protection | 1 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Warranty (Years) | 3 |
| CE Mark | Yes |
| Height / Depth | 52 |
| Length / Diameter | 78 |
| Accessories | ASBP/9 |

Technical Information

| | |
|------------------|-------------|
| Wattage | 5W |
| Lumens Delivered | 136lm |
| Beam Angle | 120 |
| CCT | 6500K |
| Input | 230V |
| Hertz | 50/60Hz |
| Operating Temp | 0°C to 45°C |

Technical Data - ETIM 6 - Emergency luminaire (EC001957)

| | |
|---|----------------|
| Mounting method | Built-in |
| With light source | Yes |
| Material housing | Aluminium |
| Colour housing | White |
| Voltage type | AC |
| Nominal voltage | 230-230 V |
| Degree of protection (IP) | IP20 |
| Protection class | I |
| Colour of light | White |
| Colour temperature | 6500-6500 K |
| Outer diameter | 78 mm |
| Lamp power | 5 W |
| Autonomy | 3 h |
| Height/depth | 52 mm |
| Type of indicator | Not applicable |
| Luminous flux at emergency operation | 136 lm |

Datasheet generated from <http://www.electrika.com> last updated Tuesday, January 23, 2018 3:28:34 PM

