



AERMLED/60/WW

Endurance LED Recessed Panel - 600 X 600 Warm White Warm White 30W White



Features

High performance maintenance free LED panel.

30W panel outperforms 3x14W T5.

Cool white and warm white options.

White anodised aluminium frame for visual compatibility with ceiling grid.

Low glare and even light distribution for multiple applications.

Panel Pod emergency option.

Panel Pod sensor option.

Surface mounting frame option.

LED lifespan L70 40,000 hours.

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Height / Depth	10
Length / Diameter	595
Width	595
Accessories	AIRMLD/POD/MWS, AIRMLD/POD/3NM/ST, AIRMLD/SMF, AIRMLD/PRK

Technical Information

Wattage	30W
Lumens Delivered	2934lm
Lm/W	98 Lm/W
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 40°C

Technical Data - ETIM 6 - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	No
Suitable for suspended mounting	No
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Material housing	Aluminium
Colour housing	White
Suitable for number of lamps	1
Voltage type	AC
Nominal voltage	230-230 V
Type of control gear	LED operating device current-controlled
Control gear included	Yes
Type of dimming	Not dimmable
Degree of protection (IP)	IP44
Protection class	II
Rated luminous flux acc. IEC 62722-2-1	2934 lm
Colour of light	White
Colour temperature	3000-3000 K
Colour rendering index CRI	80-89
Length	595 mm
Width	595 mm
Lamp power	30 W
Lamp power at multiwatt	Not applicable
Suitable for emergency lighting	No
Emergency unit integrated	No

Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
With light sensor	No
With movement sensor	No
Max. system power	30 W
Fit for monitor workplace acc. EN 12464-1	Yes
Type of grid	None
Reflector	None
Light sharing	Asymmetric
Light outlet	Direct
Beam angle	Wide beam 41-80°
Height/depth	10 mm
Ambient temperature	-10-40 °C
Suitable for light line configuration	No

Datasheet generated from <http://www.electrika.com> last updated Thursday, December 7, 2017 12:00:15 PM