



AFALED/OA/3NM/ST

Falcon LED Surface Emergency Downlight Non-Maintained - Open Area 5W White



Features

Compact surface ultra-low profile recessed self-test emergency downlight.

Self-test as standard.

Option of escape route or open area models.

High specification optic design and performance allows increased spacing providing reduced cost.

Up to 19.6 metres spacing between luminaires.

General Information

Lamp Type	LED
Colour / Finish	White
Emergency	Yes
Self Test	Yes
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Height / Depth	44.6
Length / Diameter	150
Accessories	ASBP/10

Technical Information

Wattage	5W
Lumens Delivered	152lm
Beam Angle	108
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 45°C

Technical Data - ETIM 6 - Emergency luminaire (EC001957)

Mounting method	Ceiling surface mounting
------------------------	--------------------------

Lamp type	LED not exchangeable
------------------	----------------------

With light source	Yes
--------------------------	-----

Colour housing	White
-----------------------	-------

Voltage type	AC
---------------------	----

Nominal voltage	230-230 V
------------------------	-----------

Degree of protection (IP)	IP20
----------------------------------	------

Protection class	I
-------------------------	---

Colour of light	White
------------------------	-------

Colour temperature	6500-6500 K
---------------------------	-------------

Outer diameter	150 mm
-----------------------	--------

Lamp power	5 W
-------------------	-----

Monitoring equipment	Automatic self test
-----------------------------	---------------------

Height/depth	44.6 mm
---------------------	---------

Type of indicator	Not applicable
--------------------------	----------------

Luminous flux at emergency operation	152 lm
---	--------

Datasheet generated from <http://www.electrika.com> last updated Tuesday, January 23, 2018 3:28:34 PM

