



## AMELED/OA/3NM/ST

Merlin LED Emergency Downlight Non-Maintained - Open Area 5W White



## Features

Ultra-low profile recessed self-test emergency downlight.

Self-test as standard.

Option of escape route or open area models.

High specification optic design and performance allows increased spacing providing reduced cost.

Up to 17.8 metres spacing between luminaires.

## General Information

Lamp Type	LED
Colour / Finish	White
Emergency	Yes
Self Test	Yes
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Warranty (Years)	3
CE Mark	Yes
Height / Depth	57
Accessories	ASBP/9

## Technical Information

Wattage	5W
Lumens Delivered	277lm
Beam Angle	108
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 45°C

## Technical Data - ETIM 6 - Emergency luminaire (EC001957)

<b>Mounting method</b>	Built-in
<b>With light source</b>	Yes
<b>Colour housing</b>	White
<b>Voltage type</b>	AC
<b>Nominal voltage</b>	230-230 V
<b>Degree of protection (IP)</b>	IP20
<b>Protection class</b>	I
<b>Colour of light</b>	White
<b>Colour temperature</b>	6500-6500 K
<b>Outer diameter</b>	85 mm
<b>Lamp power</b>	5 W
<b>Monitoring equipment</b>	Automatic self test
<b>Height/depth</b>	57 mm
<b>Type of indicator</b>	Not applicable
<b>Luminous flux at emergency operation</b>	277 lm

Datasheet generated from <http://www.electrika.com> last updated Tuesday, January 23, 2018 3:28:34 PM

