




PRODUCT DETAILS



Dimensions



PLAST P

PLAST P PRISMA FDH G5 2x49W, ECG, -

DOWNLOADS

[Datasheet](#)

[Product sheet](#)

[Installation manual](#)

[IES file](#)

[LDT file](#)

[EEC](#)

Description

MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	Linear fluorescent lamp T5 (FDH)
OPTICAL SYSTEM	Prismatic diffuser (PRD)
LIGHT DISTRIBUTION	Direct
WIRING	Control gear suitable for use with sensors DALI (EDA) Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (1H / 3H)
MATERIALS	Diffuser: prismatic PS Ends: white PS Housing: sheet steel
VOLTAGE	220-240 V, 50-60 Hz
NUMBER OF LAMPS	2
POWER	2 x 49 W
LAMPHOLDER	G5
EEC	A+ / A / B
PROTECTION CLASS	I
IP PROTECTION DEGREE	IP40
DIMENSIONS (L x W x H)	1540 x 200 x 70 mm
WEIGHT	3,4 kg

AREAS OF APPLICATION

EDUCATION

HOSPITALITY


HOUSE AND FLAT

INDUSTRY AND ENGINEERING



Accessories

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.