

## PRODUCT DETAILS



## Dimensions



# PLAST H

PLAST H OPAL FDH G5 1x49W, ECG, -

## DOWNLOADS

[Datasheet](#)

[Product sheet](#)

[Installation manual](#)

[IES file](#)

[LDT file](#)

[EEC](#)

## Description

<b>MOUNTING</b>	Wall mounted Surfaced / Suspended (SSx)
<b>LIGHT SOURCE</b>	Linear fluorescent lamp T5 (FDH)
<b>OPTICAL SYSTEM</b>	Opal diffuser (OPD)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (1H / 3H)
<b>MATERIALS</b>	Diffuser: PC End caps: white PC Housing: sheet steel
<b>SURFACE FINISH</b>	Housing: white RAL 9003 (W03)
<b>ACCESSORIES</b>	Rope suspension
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>NUMBER OF LAMPS</b>	1
<b>POWER</b>	1 x 49 W
<b>LAMPHOLDER</b>	G5
<b>EEC</b>	A+ / A / B
<b>PROTECTION CLASS</b>	I
<b>IP PROTECTION DEGREE</b>	IP44
<b>DIMENSIONS (L x W x H)</b>	1494 x 172 x 53 mm
<b>WEIGHT</b>	4 kg

## AREAS OF APPLICATION

EDUCATION

HOSPITALITY

HOUSE AND FLAT


INDUSTRY AND ENGINEERING



## Accessories



## LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.