




PRODUCT DETAILS



Dimensions



PLAST H

PLAST H PRISMA FDH G5 2x28W, ECG, -

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Wall mounted Surfaced / Suspended (SSx)
LIGHT SOURCE	Linear fluorescent lamp T5 (FDH)
OPTICAL SYSTEM	Prismatic diffuser (PRD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (1H / 3H)
MATERIALS	Diffuser: PC End caps: white PC Housing: sheet steel
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Rope suspension
VOLTAGE	220-240 V, 50-60 Hz
NUMBER OF LAMPS	2
POWER	2 x 28 W
LAMPHOLDER	G5
EEC	A+ / A / B
PROTECTION CLASS	I
IP PROTECTION DEGREE	IP44
DIMENSIONS (L x W x H)	1194 x 172 x 53 mm
WEIGHT	3,3 kg

AREAS OF APPLICATION  **EDUCATION**

 **HOSPITALITY**

 **HOUSE AND FLAT**


 **INDUSTRY AND ENGINEERING**



Accessories



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.