




PRODUCT DETAILS



Dimensions



Accessories



EXE II PAR MAT-V2 (TWIN) FDH G5 2x28W, ECG, RAL 9003

DOWNLOADS

[Datasheet](#)

[Product sheet](#)

[Installation manual](#)

[EEC](#)

Description

MOUNTING	Ceiling surfaced / suspended (SSx)
LIGHT SOURCE	Linear fluorescent lamp T5 (FDH)
OPTICAL SYSTEM	Parabolic louvre PAR MAT-V2 TWIN (MW2)
LIGHT DISTRIBUTION	Direct Direct-indirect
WIRING	Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (1H / 3H)
MATERIALS	Housing: sheet steel Parabolic louvre: matt aluminium
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Pull switch Rope suspension
VOLTAGE	220-240 V, 50-60 Hz
NUMBER OF LAMPS	2
POWER	2 x 28 W
LAMPHOLDER	G5
EEC	A+ / A / B
PROTECTION CLASS	I
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1250 x 160 x 56 mm
WEIGHT	3,5 kg

AREAS OF APPLICATION

 EDUCATION

 OFFICE





LIDC

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.