

Premier DX200 & CF20

Centrifugal extract and condensation control fans



DX200



CF20

The Range

Premier range of centrifugal fans is designed specifically for domestic applications including bathrooms, shower rooms, toilets and utility rooms where longer duct runs are required.

All models have a gloss white casing with a clean and sleek appearance. A two part casing means Premier fans can be recess or surface mounted. All models feature an automatic air operated backdraught shutter.

The clip-off front cover and removable fan blade on all models allow easy cleaning and maintenance. All models also have a neon indicator.

DX200 and CF20 models are IPX5 rated and BEAB approved. They are all suitable for 220-240V AC 50Hz mains operation. Motors are totally enclosed and maintenance free for life, with self aligning bearings and a thermal cut-out. All electronics and wiring terminals are fully protected.

Key Features

- Available in DX extract or CF humidity control models
- Room size performance speed selector, boost and trickle ventilation settings on selected models
- Adjustable humidistat on condensation control models
- Quick visit delay feature on multi-speed timer models
- Automatic air operated backdraught shutter fitted
- Can be surface or recess mounted
- Totally enclosed maintenance free for life motors
- Clip-off front cover and fan blade for ease of cleaning and maintenance
- IPX5 rated
- BEAB approved

Product Selector	DX200	DX200T	CF20	CF20T	
Reference number	91013AW	91014AW	91015AW	91016AW	
Speeds	2	4	5	5	
Trickle ventilation facility		■	■	■	
Max. electrical power rating (W)	34	34	34	34	
IP rating	IPX5	IPX5	IPX5	IPX5	
Weight (kg)	2.2	2.2	2.2	2.2	
UK Guarantee (years)	2	2	2	2	
Extract performance (FID, m ³ /h)	boost	-	108	108	
	speed 3	-	108	102	
	speed 2	108	79	79	79
	speed 1	50	50	50	50
	trickle	-	36	36	36
Extract performance (FID, l/s)	boost	-	30	30	
	speed 3	-	30	28	28
	speed 2	30	22	22	22
	speed 1	14	14	14	14
	trickle	-	10	10	10
Sound pressure (dB(A)@3m)	boost	-	50	50	
	speed 3	-	50	48	48
	speed 2	50	42	42	42
	speed 1	32	32	32	32
	trickle	-	26	26	26

Models

Premier DX200

Ref. 91013AW

High performance centrifugal unit | Choice of 2 set speeds

Premier DX200T

Ref. 91014AW

High performance centrifugal unit with timer | Room size selector matches extract performance for improved efficiency | Quick visit delay feature prevents fan from running should light be switched On/Off again within 2 mins | Mechanical trickle ventilation facility | Built-in run-on period after light switched off | User adjustable from 30 sec-20 mins

Premier CF20

Ref. 91015AW

High performance condensation control centrifugal unit | Step-speed, user adjustable humidistat | Room size selector matches extract performance for improved efficiency | Tricklevent and pullcord manual override | Includes external wall grille

Premier CF20T

Ref. 91016AW

All the features of CF20 plus: Auto run-on after light switched off | Quick visit delay feature prevents fan from running should light be switched On/Off again within 2 mins

Ancillaries

See pages 72-87

Dimensions (mm)

