


Description	Size (mm <sup>2</sup> )	Voltage Grade (kV)
<b>Cu/XLPE/SWA/PVC</b>	<b>4X120</b>	<b>0.6/1 (1.2)</b>

Applicable Standards	Application
BS EN 60228 BS 5467	For outdoor and indoor fixed installations and it's normally used for power distribution in urban networks and industrial plants. Suitable for laying underground directly or in ducts or on trays in free air.



Features	Cable Identification	Construction
Conductor Operating Temp. up to 90 °C Conductor Short Circuit Temp. up to 250 °C	<b>Cores Identification</b> Brown , Black , Grey , Blue  <b>Outer Sheath Color</b> Black  <b>Marking Over the Outer Sheath</b> EL SEWEDY CABLES 140/001 BASEC ELECTRIC CABLE 4X120 mm2 600/1000 V Cu/XLPE/SWA/PVC BS 5467 CE Manufacturing Year H	<b>Conductor</b> Sector Shaped Stranded Compacted Copper (Class 2) <b>Insulation</b> XLPE (GP 8) <b>Inner Sheath</b> PVC <b>Armour</b> Steel Wire Armour <b>Outer Sheath</b> PVC (Type 9)

Electrical Data		
Conductor Max. DC Resistance at 20°C	0.153	Ω/km
Conductor Max. AC Resistance at 90°C	0.1964	Ω/km
Conductor Short Circuit Current for 1 sec.	17.2	kA
Rated Current (laid in Air) *	393	A
Rated Current (laid in Duct) *	301	A
Rated Current (laid in Ground) *	397	A

General Data		
Nominal Cable Diameter	44.6	mm
Approximate Cable Weight	6525	kg/km
Minimum Bending Radius	8 × Outer Diameter	

\* Air Temperature = 30 °C , Ground Temperature = 20 °C , Soil Thermal Resistivity = 1 °C.m/W , Burial Depth = 0.5 m

Testing	Packing
All routine tests required by BS 5467 will be performed on the cable and a test certificate will be supplied on request.	<b>Standard Cutting Length</b> 1000 (±3%) m <b>Drum Type</b> Wooden Drum