



# CorePro LEDcandle

## Corepro Candle ND 4-25W E14 827 B35 CL

The frosted CorePro LEDcandle is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E14 holder and is an attractive product for chandeliers. LEDlamps deliver huge energy savings and minimize maintenance cost.

### Product data


General Information		Starting time (nom.)	
Cap base	E14 [ E14]		0.5 s
Red Dot Design Award winner mark	Reddot Design Award Winner 2016	Warm-up time to 60% light (nom.)	0.5 s
Nominal lifetime (nom.)	15000 h	Power factor (nom.)	0.4
Switching cycle	50000X	Voltage (Nom)	220-240 V
Technical type	4-25W	<b>Temperature</b>	
<b>Light Technical</b>		T-Case maximum (nom.)	75 °C
Colour code	827 [ CCT of 2700K]	<b>Controls and Dimming</b>	
Luminous flux (nom.)	250 lm	Dimmable	no
Luminous flux (rated) (nom.)	250 lm	<b>Mechanical and Housing</b>	
Colour designation	Warm white (WW)	Bulb finish	Clear (CL)
Correlated colour temperature (nom.)	2700 K	<b>Approval and Application</b>	
Luminous efficacy (rated) (nom.)	62.50 lm/W	Energy efficiency label (EEL)	A+
Colour consistency	<6	Energy Consumption kWh/1000 h	4 kWh
Color rendering index (nom.)	80	<b>Product Data</b>	
LLMF at end of nominal lifetime (nom.)	70 %	Full product code	871869650757500
<b>Operating and Electrical</b>		Order product name	Corepro Candle ND 4-25W E14 827 B35 CL
Input frequency	50 to 60 Hz	EAN/UPC – product	8718696507575
Power (Rated) (Nom)	4 W	Order code	50757500
Lamp current (nom.)	35 mA		
Wattage equivalent	25 W		

# CorePro LEDcandle

Numerator – quantity per pack	1
Numerator – packs per outer box	10
Material no. (12NC)	929001142202

Net weight (piece)	0.040 kg
--------------------	----------




## Dimensional drawing



Product	D	C
Corepro Candle ND 4-25W E14 827 B35 CL	35 mm	106 mm

LED ND 4-25W E14 827 220-240V B35 CL

## Photometric data



## CorePro LEDcandle

### Lifetime



LEDbulb 60W E14 827 FR B38



LEDbulb 60W E14 827 FR B38

