



AZTEC

High-output IP65 LED high-bay fitting



AZTEC 240W



APPLICATIONS

- Industrial production areas
- Retail sheds
- Public areas in airports, railway stations and coach termini

CONSTRUCTION

- Die-cast aluminium main body, painted matt black
- Toughened glass front panel, secured with a black painted steel trim
- Gasket between glass panel and body to ensure the IP65 rating
- Pre-wired with 380mm of H05 flex

TECHNICAL DETAILS

- Philips high-power LEDs mounted on a metal core PCB
- **Three wattages available:**
 - 100W nom., 97W act., 12,860 lm, 133 l.lm/c.W
 - 150W nom., 146W act., 20,080 lm, 137 l.lm/c.W
 - 240W nom., 238W act., 34,320 lm, 144 l.lm/c.W
- CRI >80
- CCT 4000K
- Beam angle 112°

OPTIONS

BEAM ANGLE For other beam angles, please enquire for availability.

WEIGHT

- 100W, 3.4Kg
- 150W, 5.2Kg
- 240W, 6.7Kg

ORDER CODE	DESCRIPTION
NAC100/840	AZTEC 100W LED UFO HIGH BAY IP65 COL840
NAC150/840	AZTEC 150W LED UFO HIGH BAY IP65 COL840
NAC240/840	AZTEC 240W LED UFO HIGH BAY IP65 COL840

