

NEBRASKA

IP65 LED slim emergency bulkhead with a range of attachments



NEBRASKA LED



NEBRASKA SEMI-RECESSED MOUNTING KIT



NEBRASKA HINGED GEAR TRAY WITH QUICK-RELEASE CATCHES



STANDARD LEGENDS AVAILABLE AS UP, DOWN, LEFT & RIGHT



"MAN RUNNING THROUGH DOOR" V2 LEGENDS AVAILABLE AS UP, DOWN, LEFT & RIGHT



APPLICATIONS

- Corridors
- Exits
- Escape routes

CONSTRUCTION

- Polycarbonate base and cover
- Cover fitted to base with stainless steel screws in threaded brass inserts
- Hinged gear tray
- Supplied with standard ("Man running towards door") legend pack.
- 20mm conduit entry
- 3 x NiCd 3.6V, 1,500 mAh cells

SPECIFICATION

- 2W LED M3
 - 116 lm, 2.6W
- 3 hours operation on battery power after mains failure
- 20m maximum viewing distance with standard legends
- 30m maximum viewing distance with drop-down attachment

OPTIONS

SELF TEST Also available in a Self Test version. Add suffix ST

MOUNTING KIT Semi-recessed mounting kit available. Cut-out 360 x 120mm. Order as a separate item.

LEGENDS Spare legend packs available.

Alternative legend pack available as listed - to be ordered as a separate item.

For "man running through door", use suffix V2, as listed.


All variants may be installed as maintained or non-maintained variants. Full details and wiring diagrams supplied in instruction leaflet.

Drop-down attachment available, to be ordered as a separate item.


PLEASE NOTE THAT:

- Because the frequency of charge & discharge is beyond NVC's control, batteries are excluded from the 5 year warranty on this product
- NiCd cells will not perform well below 0°C

NEBRASKA V3 WITH DROP DOWN ATTACHMENT



NEBRASKA V3



| ORDER CODE | DESCRIPTION |
|-----------------|--|
| NNE/2/LED/M3/V3 | NEBRASKA V3 2W LED IP65 MAINT 3HR |
| ATTACHMENTS | |
| NNE/RMK/V3 | NEBRASKA V3 RECESSED MOUNTING KIT |
| NNE/DDA/V3 | NEBRASKA DROP DOWN ATTACHMENT C/W LEGEND PACKS |
| NNE/V2/LEP4 | NEBRASKA V2 LEGEND PACK OF UP DOWN LEFT RIGHT |