

LIGHTING

Product Catalogue

In House Lighting Specialists

Our lighting experts can design and specify the best lighting solution for the customers' needs using the best packages available that includes Lighting Reality, Relux & Dialux.

This entails checking to see how many and what type of fittings would be required to light a certain space to conform to best practice and meet any regulations relating to the intended use of that space.

We are available to assist with:

- Developing commercial lighting plans
- Recommending product selection
- Calculating payback periods
- Consulting to improve energy efficiency and building energy performance ratings
- Sensitivity setting no
- Remote controllable EE807, EE808

Also through our technical lighting division, Astrotek we can provide conceptual and detailed design services to end-users, specifiers and contractors and have done for over 20 years. Furthermore we can source high quality solutions to provide a complete design and supply service. Our core areas of expertise are in commercial, medical, pharma, retail, and industrial/infrastructure applications as well as educational and high spec residential. Our team of designers particularly enjoy projects requiring bespoke or customised solutions.

Engineers:

We provide comprehensive design resources, high quality product range and competitive prices which enable us to meet the needs of our clients as well as the requirements of the end-user. We are also aware of the importance of back up and support during the whole working process to ensure that the project will be successful in terms of quality and time.

Architects & Interior Designers:

Architecture needs to respond creatively to contemporary cultural, economic, social and environmental factors. We fully understand the challenges which architects have to face and the importance of architectural work in modern times.

We fully understand the importance of luminaires which have to be integrated into the architectural design to create the big picture and to bring the architectural work to perfection. We see it as our objective to supply architects with high quality and innovative products which support the architectural concept. Furthermore we want the finished product to have a positive effect on everyone who experiences it. That's why we want to be a part of the big picture to make architectural concepts happen and to provide the architectural concept with its principal beauty, LIGHT.

Our core areas of expertise:



- Commercial
- Medical
- Pharma / Cleanroom
- Retail
- Infrastructure / Government
- Industrial applications
- High educational and specification residential

TRAFFIK R LED

Professional streetlight luminaire for LED light sources.

Technical Data

Mounting: on outriggers ø60/48mm,
on pillar ø60/48mm
Body: high pressure die-cast aluminum
Colour: grey





5YR
WARRANTY

Product Codes	Description
2763150	130292.5LO21.011 TRAFFIK R LED ED 4600LM/740 IP66 027 GREY
2763151	130292.5LO31.011 TRAFFIK R LED ED 6900LM/740 IP66 027 GREY
2763152	130292.5LO41.011 TRAFFIK R LED ED 9000LM/740 IP66 027 GR
2763154	TRAFFIK R LED ED 6900LM/740 IP66 027 GREY W/NEMA SOCKET
2763155	TRAFFIK R LED ED 9000LM/740 IP66 027 GREY W/NEMA SOCKET

URBINO LED

Technical Data

Mounting: on pillar ø60/48mm,
Body: high pressure die-cast aluminum
Lateral Surface Wind Exposed: 0.039 m²
Colour: grey
RAL: 7035



5YR
WARRANTY

Product Codes	Description
2763121	URBINO LED 55W 6250LM/757 GREY
2763122	URBINO LED 84W 10000LM/757 O7 GREY
2763123	URBINO LED 110W 13300LM/757 O7 GREY
2763124	URBINO LED 55W 6250LM/757 O7 GREY W/PHOTOCELL
2763125	URBINO LED 84W 10000LM/757 O7 GREY W/PHOTOCELL
2763126	URBINO LED 110W 13300LM/757 O7 GREY WPHOTOCELL

AVENIDA LED

For pedestrian zones graphite II.
Park luminaire in modern form for LED light sources.

Technical Data

Mounting:	on pillar ø48/60/76mm, with mounting bracket (included)
Body:	high pressure die-cast aluminum
Lateral Surface Wind Exposed:	0,088 m ²
Colour:	graphite
Operating temperature range [°C]:	-40 ... +50

Electrical Data

Power supply efficiency:	>89%
Power:	220-240V 50/60Hz
Includes light source:	yes
Output current [mA]:	200-700
Type of equipment:	ED
Light source / lamp:	LED
Electrical connection:	luminaire equipped with 2x1,5 mm ² wire with a length of 6 m (II class)

Optical Data

Light distribution:	omnidirectional
Way of lighting:	direct
Type of optic:	O17 - for pedestrian zones
Diffuser:	polycarbonate
CRI/Ra:	>80
Lumen luminaire [lm]:	4400
Colour	

General Data

Lifetime (L80B10):	75 000 h
Available on request:	DALI, LLOC, twilight sensor, 10kV surgeprotection, NTC
Other remarks:	the pole is not part of the luminaire
Application:	avenues, sidewalks, parks, residential, public spaces, playgrounds, promenade, residential area roads

5YR
WARRANTY

Product Codes	Description
2763141	AVENIDA LED 40W 4400lm 4000K IP66 O17



Street Lighting - 'Council approved'

CREE 

XSP HIGH OUTPUT SERIES

XSPM - LED Street/Area Luminaire

Designed from the ground up as a totally optimized LED street lighting system, XSPM maintains the familiar look of the traditional cobrahead design and delivers substantial energy savings while reducing maintenance time and costs. Equipped with our NanoOptic® Precision Delivery Grid™ optic, XSPM achieves better optical control than traditional street lighting fixtures and efficiently delivers white uniform light for safer-feeling communities. The luminaire is designed to mount directly to 76mm or 60mm outer dimension tenons or poles with a specific spigot (adjustable arm).

Applications: Roadway, parking lots, walkways and general area spaces


Performance Summary

NanoOptic® Precision Delivery Grid™ optic	Initial Colour consistency: Class 1 - 10 years on luminaire / 10 years on Colorfast DeltaGuard® finish
Efficacy: Up to 145 lm/W	Limited Warranty†: Class 2 - 5 years on luminaire / 10 years on Colorfast DeltaGuard® finish
CRI: Minimum 70 CRI	
CCT: 3000K; 4000K; 5700K	

Contact Darren Becton for prices and ordering codes









6MT OCTAGONAL POLE




Product Codes	Description
2333424	6M STEEL PUBLIC LIGHTING COLUMN "OCTAGONAL"

8MT OCTAGONAL POLE




Product Codes	Description
2333425	8M STEEL PUBLIC LIGHTING COLUMN "OCTAGONAL"

COLUMN




Product Codes	Description
2333484	6MT X 76MM GALV COLUMN
2333483	5MT X 76MM GALV COLUMN

OUTREACH




Product Codes	Description
2333495	700MM STRAIGHT OUTREACH

PILLAR



Product Codes	Description
2333496	ESB MICRO PILLAR



Product Codes	Description
2333497	ESB MINI PILLAR

CRUISER 2 LB LED

Industrial luminaire for LED light sources.

Technical Data

Mounting:	surface mounted, in the ceiling, with mounting frame (sold separately), suspended, on chains (on request), for hanging on a cable, with special mounting bracket (on request)
Body:	high pressure die-cast aluminum
Colour:	grey
Replacement of conventional technology [W]:	250W MH (300W)
Diffuser:	Tempered glass
Colour Temperature [K]:	4000
Additional information:	Ball impact resistance.



Product Codes	Description
2762002	CRUISER 2 LB LED 20000LM/840 IP65 1000DEG. GRAY

AZTEC V2

High-output IP65 LED high-bay fitting.

Applications

- Industrial production areas
- Retail sheds
- Public areas in airports, railway stations and coach terminals

Construction

- Die-cast aluminium main body, painted matt black
- Gasket between PC panel and body to ensure the IP65 rating
- Pre-wired with 1m of H05 flex

Technical details

- Philips high -power LEDs mounted on metal core PCB
- Three wattages available:
 - 100W, 14,940 lm at 106W, 141 l.lm/c.W
 - 150W, 19,815 lm at 146W, 136 l.lm/c.W
 - 220W, 30,720 lm at 222W, 138 l.lm/c.W
- CRI > 80
- CCT 4000K
- Beam angle 112°
- Weight:
 - 100W - 3,4kg / 150W - 5,2kg / 220W - 6,7kg



Product Codes	Description
2702010	AZTEC V2 100W LED UFO HIGH BAY IP65 COL840 14,940 lm
2702011	AZTEC V2 150W LED UFO HIGH BAY IP65 COL840 19,815 lm
2702012	AZTEC V2 220W LED UFO HIGH BAY IP65 COL840 30,720 lm

GLOBO 14 WATT

Housing: vandal resistant, self-extinguishing, UV-stabilised anti-yellowing polycarbonate and external finishing ring in ABS. Diffuser: vandal resistant, self-extinguishing, UV-stabilised anti-glare polycarbonate; dustproof.

LED: Power factor: 0,9 Luminous flux maintenance 80%: 50.000h (L80B20)



5YR
WARRANTY

Product Codes	Description
2565101	1844 427249-00 GLOBO 2.0 LED 14W WHITE 4K IP65
2565102	1844 427249-19 GLOBO 2.0 LED 14W SENSOR WHITE 4K IP65
2565103	1844 427249-31 GLOBO 2.0 LED 14W 3H EM WHITE 4K IP65
2565104	1844 427249-31-001098 GLOBO 2.0 LED 14W 3H EM + SEN WH 4K IP



15W LED 2D



5YR
WARRANTY

IP
65



L1

L2

Product Codes	Description
2755101	15W LED 2D, IP65, White
2755102	15W LED 2D, IP65, White, Emergency
2755103	15W LED 2D, IP65, White, Sensor
2755104	15W LED 2D, IP65, White, Sensor and Emergency

SPARTAN

IP65 polycarbonate LED bulkhead fittings

Specification


- 15W, 1,310 lm, 86 l.m/w
- CCT 5000K
- SMD LEDs on metal core PCB

Construction

- Polycarbonate base/opal diffuser
- Gasket between base and diffuser to ensure IP65 rating
- Gear tray retained on strap for easy installation
- Optional polycarbonate bezels and eye-lid covers available in white or black. See accessories below



Optional snap-on
plain or eyelid bezels
white or black available
separately



Product Codes	Description
2705034	NSPS15/LED/WH/850 SPARTAN 15 LED IP65 WHITE BASE
2705035	NSPS15/LED/BK/850 SPARTAN 15 LED IP65 BLACK BASE
2705036	NSPS15/LED/WH/M3/850 SPARTAN 15 LED IP65 +M3 WHITE BASE
2705037	NSPS15/LED/BK/M3/850 SPARTAN 15 LED IP65 +M3 BLACK BASE
Accessories	Description
2705038	NSP/BEZEL/WH SPARTAN BEZEL TRIM WHITE
2705039	NSP/BEZEL/BK SPARTAN BEZEL TRIM BLACK
2705040	NSP/EYELID/WH SPARTAN EYELID TRIM WHITE
2705041	NSP/EYELID/BK SPARTAN EYELID TRIM BLACK

BRONX SLIM


IP65 die-cast aluminium and polycarbonate LED bulkhead for commercial outdoor areas.

Applications

- For commercial exterior use on walkways, entrances and building perimeters

Specification

- Die-cast aluminium base with side or rear entry points for mains cabling
- Supplied with IP65 rated cable gland
- Polycarbonate cover, hinged and retained with stainless steel screws



Product Codes	Description
2703009	NBX30SL/LED/840 BRONX SLIM 30W LED WALL PACK
2703010	NBX30SL/LED/PEC/840 BRONX SLIM 30W LED W//PHOTO

MINICOMFORT LED 841

State-of-the-art light source for greater efficiency and Dark Light optics for controlled light emissions (luminance < 500 cd/m² for radial angles > 65°). Absolutely no glare and colours are perceived as if they were viewed under natural light conditions,

Technical Data


- Housing:** in galvanised steel sheet panles, pre-coated with polyester resin
Cover: with steel panels
Equipment: hinged door and quick clamping Mechanism,
Warranty: with protective film on fixture and baffle louvre. Supplied without bracketas: for non-surface mounted versions, use bracket acc. 326.
On request: integrated multi-sensor, order with subcode -0092 (1-10V).



Product Codes	Description
2561474	153535-00 LED 4x, 3,5kg, W 33, 4000 K - 4900lm - CR>89

842 LED Panel UGR < 19

80% lumen maintenance for 50000 h (L80B20), perfect colour rendering (CRI80 or CRI>90), no glare (UGR<19) and certified low flickering level. Housing and frame: housing in galvanised steel sheet, and frame in aluminium. Inner slab: in PMMA. Diffuser: extruded in prismatic engineering plastic with high thermal transmittance. UGR glare index: UGR<19 (in any situation). - EN 12464. Power factor 0.95 Luminous flux maintenance 80% 50.000h (L80B20).



Product Codes	Description
2561487	842 150205-00-3600lm-4000K-CRI80 600X600 LED PANEL WHITE

LUGCLASSIC LB LED p/t

Optical Data

Diffuser:	opal plexiglass (PLX)
CRI/Ra:	≥80
Lumen LED [lm]:	5100
Lumen luminaire [lm]:	4350
Temperature [K]:	4000
UGR:	<19

General Data

Lifetime (L80B10):	100 000 h
Lifetime (TM21 L90B10):	30 000 h
Operating temperature range:	0°C ... +40°C
Application:	offices, classrooms, auditorium



Product Codes	Description
2761472	00061.00150 LUGCLASSIC LB 600X600 33W 4700LM

Rexel 40W LED PANEL



- Suitable for use in offices, shops, reception areas, restaurants, hotels, schools, hospitals
- LED replacement for 4x18W T8 lay-in modular fittings
- Fits into standard sizes of ceiling grid - 15mm and 24mm
- Up to 5 times that of a standard fluorescent lamp
- Driver complete with male and female loop in/out connectors included for fast fix installation

Comparable to T8

Fluorescent (W):	4x18
Total Power (W):	40
Total Light Output (lm):	3,500
Efficacy (lm / cctW):	88
Rated Life (hrs):	50,000
CCT (K):	4,000
CRI (Ra):	80



600 x 600mm



300 x 1,200mm



600 x 1,200mm



Product Codes	Description
2751401	Standard, 4000K - 32507 lumen
2751402	Standard, 5000K - 3585 lumen
2751409	Emergency, 4000K

Product Codes	Description
2751403	Standard, 4000K - 3381 lumen

Product Codes	Description
2751405	Standard, 4000K - 5336 lumen

MERCURY MKII LED

The Mercury MKII LED range offers a sleek option, where DHSS recommendations are required to be met. The IP44 rating reduces dust and insects entering the fitting. The end caps are fixed in-place via a stainless steel screw which can be replaced with a tamper proof screw making the fitting anti-tamper.

- IP44
- Screwed end caps
- Covered gear tray
- Rated 125 lumen per watt
- UGR19
- Listed on the SEAI Triple E website under LIG 87465
- CRI80



Product Codes	Description
2631001	SGL/LED/15/5350/MC/MKII/DALI 29W 4600LM LED SUR. FTG DALI
2631002	SGL/LED/15/5350/MC/MKII 29W 4600LM LED SURFACE FTG
2631003	SGLLED155350MCMKIIV2 DALI 29W 4600LM LED SUR W/5M 5 CORE FLEx
2631004	SGLLED155350MCMKIIV2 29W 4600LM LED SUR FTG W/5M 3 CORE FLEX

ECI PRELUX CAMPUS

The 58W 5ft Campus surface luminaire is designed specifically for academic buildings. Also available in emergency mode, this slim, contemporary style twin surface fitting provides an efficient 100Lm/W and an excellent quality of luminance for learning environments.

Ideal Application Areas Include:

Schools/Colleges, Office Developments, Retail Premises, Hotels and Leisure Facilities, Hospitals and Public Buildings.



Specification

Dimensions: 1490*200*81mm
Input Voltage: 180-240V 50/60Hz
Input Power: 58W Standard / Emergency
Lumens (35%) 5800 (35%) 5800
No. of LEDs: 320pcs SMD
Color Rendering Index: >80


CCT: 4000K
Protection: IP20
Certification: CE, EMC, LVD
Lifetime: 50,000 Hours
Emergency Mode: 3 Hours @ 3W
Battery Warranty: 2 Years



Product Codes	Description
2751020	5FT 58W 5800LM LED FLAT-BACK FITTING

NVC PHOENIX

LEDs behind a slim opal diffuser, mounted on a traditional batten body. Available in 4', 5' and 6', standard and high-output - a direct replacement for traditional single and twin battens.



Product Codes	Description
2700053	NPH65/LED/850 5FT HIGH OUTPUT 65W PHOENIX LED BATTEN

ROBUS TOUCAN 45W LED Batten

- Suitable for use in flat and apartment blocks, public buildings, care homes, communal areas, reception areas
- LED replacement for 1x70W T8 fluorescent surface fittings
- Low profile aluminium housing with PBT end caps and polycarbonate diffuser
- High impact rating of IK08
- Complete with stainless steel mounting brackets
- Prewired with 1m of flex
- High efficacy of 100lm/W
- Wide operating ambient temperature range of -20°C to +40°C
- Suitable for switching by PIR, Microwave or Photocell



Product Codes	Description
2080154	TOUCAN 18W LED BATTEN, 0.6M, IP20, WHITE, 4000K
2080155	TOUCAN 36W LED BATTEN, 1.2M, IP20, WHITE, 4000K
2080156	TOUCAN 45W LED BATTEN, 1.5M, IP20, WHITE, 4000K

Corrosion

Beghelli

BS100 LED ADJUSTABLE

Waterproof ceiling light

High performance fixture with high flux and no glare screen. Suitable for emergency with related accessories, inverter with signalation led. The fixture is equipped with a 4 position switch driver. It lets the luminaire to change light output to 4 different fixture providing a versatile solution. Fixture body is composed of self-extinguishing polycarbonate, UV stabilized and screen is designed to spread light in the no glare best way. Fixture is suitable for outdoor installations and industrial environments thanks to a special gasket and closing hooks.

8000 lm

7500 lm

7000 lm

6500 lm

5YR
WARRANTY


L
1580



Product Codes	Description
2090369	40005 59W BS100 LED ADJ L1580MM 6500/7000/7500/8000LM - 4000k
2611502	BS100 47W LED ED 4000K C/PROOF 1500MM W/EMER

927 ECHO - TWIN BODY LED

aisano
illuminazione



690/1300/1600

152

102

5YR
WARRANTY

Product Codes	Description
2560347	164705-00 927 ECHO LED WHITE 48W, 2,63 kg. Lamps: 7780lm-4000K-CRI 80, Colour GREY
2560350	164705-31 927 ECHO LED EMERGENCY 3H, 3,63 kg. Lamps: 7780lm-4000K-CRI 80, Colour GREY



CLEVELAND

Polycarbonate IP65 weather-proof LED fittings

Applications

- Industry, garages & workshops
- Food preparation areas

Specification

- Polycarbonate base and opal diffuser
- Grade 316 stainless steel clips
- Aluminium heat-sink
- Stainless steel surface mounting clips
- Can also be suspended from wire/chain using clips provided
- Twin 57W, 6,600 lm, 114 l.lm/c.W
- CRI >80 / CCT 4000K



Product Codes	Description
2700394	NCV1X5/840 Cleveland LED Single 5Ft IP65 840
2700395	NCV1X5/M3/840 Cleveland LED Single 5Ft IP65 M3 840
2700392	NCV2X5/840 Cleveland LED Twin 5Ft IP65 840
2700393	NCV2X5/M3/840 Cleveland LED Twin 5Ft IP65 M3 840



ATLANTYK LB LED

Technical Data

Operating temperature range [°C]: -20 ... +35

Optical Data

Way of lighting: direct
Diffuser: polycarbonate CRI/Ra: ≥80
Lumen LED [lm]: 7100
Lumen luminaire [lm]: 6050
Temperature [K]: 4000

General Data

Lifetime (L80B10): 60 000 h
Additional information: stainless steel clips included
outdoor use only under a cover, do not expose to direct sunlight and rain
Other remarks: parking areas, production halls, electricity plants, roofing



Product Codes	Description
2760340	300090.00062 ATLANTYK LB LED 1640 ED 7100LM/840 PC OPAL IP65



ECO LEX, ECO LEX 2 & ECO LEX 3

Eco Lex LED is a new series of recessed spotlights that combines advanced technology and energy savings with an easy-to-install, low cost, robust and durable fixture. They cover a wide range of cutout holes.

Housing: in die cast aluminium

Diffuser: The shield consists of a laser-cut slab that serves as a lens for its effect of concentric circles. These decorations create a pattern, with variable distances; the closer they get to the centre, the closer they come together achieving excellent visual comfort without glare.

Painting: dust painted, using polyester epoxy paint to withstand UV rays.

Luminous flux maintenance 80%: 50.000h (L80B20).



Product Codes	Description
2555387	22172904-00 ECO LEX LED IP44 11W 1088LM 4K 90-96MM CUTOUT
2555388	22172915-00 ECO LEX 2 LED IP44 14W 1308LM 4K 170-190MM CUTOUT
2555386	22172916-00 ECOLEX 3 LED 1729 21W 2190LM 4k 198- 216MM CUTOUT

LUGSTAR LB LED GEN.2 p/t



Decorative downlight luminaire for suspended ceilings, degree of water and dust-proof IP20 and IP44, for LED light sources, UGR<19

Technical Data

Mounting: in the ceiling, with mounting brackets (included)
Body: aluminum
Colour: white

Additional Info

Operating temperature range: 0 °C ... +25 °C
Lifetime (L70B50): 50 000 h

General Data

Application: shopping centers, museums, galleries, exhibitions, exhibitions, offices, hotels, public utility facilities



Product Codes	Description
2765302	300031.00008 LUGSTAR LB LED RECESSED ED 3000LM/840 IP44 70DE 215mm cut out

LUGSTAR SPOT LB LED

Decorative downlight luminaire for suspended ceilings, for LED light sources.

Technical Data

Mounting:	in the ceiling, with mounting brackets (included)
Body:	plastic
Colour:	white
Diffuser:	opal plexiglass (PLX)

Optical Data

Reflector:	white, aluminum mat faceted
-------------------	-----------------------------

General Data

Lifetime (L80B10):	30 000 h
Other remarks:	Mounting in ceilings 8-25 mm ² thick
Application:	shopping centers, halls, corridors, museums, galleries, exhibitions, exhibitions, offices, hotels, public utility facilities



Product Codes	Description
2765309	300031.00107 LUGSTAR LB SPOT LED IP44 ED 1600LM 4000K ALU MATT 155mm cutout



5W FIRE-RATED DIMMABLE DOWNLIGHT

Applications

- Suitable for use in domestic and commercial fire-rated applications such as living, bathroom and bedroom spaces, hotels and office reception areas, shops, pubs and restaurants

Specification


- LED Replacement for 50w halogen lamp
- Dimmable
- 30, 60 & 90 minutes fire tested
- Suitable for switching by PIR, Microwave sensor or photocell



Product Codes	Description
2755312	5W Fire-rated Dimmable Downlight, 3000K, IP65, Dimmable, White
2755313	5W Fire-rated Dimmable Downlight, 4000K, IP65, White

TRIUMPH

Cutout 70mm, Overall DIA 98mm, Depth 92mm

5YR
WARRANTY

Product Codes	Description
2085291	RATR8P04038-01 TRIUMPH 8W IP65 DIMMABLE LED DOWNLIGHT 4000K
2085290	RATR8P03038-01 TRIUMPH 8W IP65 DIMMABLE LED DOWNLIGHT 3000K



SPARK LED

Recessed modern downlight, for suspended ceilings with adjustable optics for integrated LED modules.

Technical Data

Mounting:	in the ceiling, with mounting brackets (included)
Body:	high pressure die-cast aluminum
Colour:	white

Electrical Data

Power supply efficiency:	>89%
Power:	220-240V 50/60Hz
Includes light source:	yes
Type of equipment:	ED
Electrical connection:	max 2x1,5 mm wire

Optical Data


Light distribution:	circular
Way of lighting:	direct
Reflector:	aluminum polished faceted

Additional Info

Available on request:	DALI
Operating temperature range:	0 °C ... +35 °C
Lifetime (L70B50):	50 000 h

General Data

Application:	boutiques, delicatessen, jeweler, shopping centers, supermarkets, museums
---------------------	---


5YR
WARRANTY

Product Codes	Description
2765336	030361.5L05.303 SPARK LED RECESSED ED 4050LM/830 39° Whi

LED OUTDOOR FLOODLIGHT COMMERCIAL / INDUSTRIAL


The industrial floodlight range is ideal for both industrial and commercial applications offering equivalents up to 250W SON/MH, whilst offering significant energy savings over discharge light fittings with a similar size and shape to traditional commercial floodlights, these are ideal for retrofit applications.

- Materials
 - Aluminium housing and body
 - Glass diffuser
- Mounting bracket for 180° tilt
- Features a beam angle of 100°
- Photocell option available to turn fitting off when there is enough natural daylight



Product Codes	Description
2752633	LDV F7040B FLOODLIGHT 70W/4000K BK IP65, Wattage (W) 70, Lumens (lm) 7700, Efficacy (Lm/W) 110
2752636	LDV F7040BP FLOODLIGHT 70W/4000K PHTC BK IP65, Wattage (W) 70, Lumens (lm) 7700, Efficacy (Lm/W) 110
2752632	LDV F9040B FLOODLIGHT 90W/4000K BK IP65, Wattage (W) 90, Lumens (lm) 10000, Efficacy (Lm/W) 110
2752637	LDV F9040BP FLOODLIGHT 90W/4000K PHTC BK IP65, Wattage (W) 90, Lumens (lm) 10000, Efficacy (Lm/W) 110
2752634	LDV F13540B FLOODLIGHT 135W/4000K BK IP65, Wattage (W) 135, Lumens (lm) 15000, Efficacy (Lm/W) 110
2752638	LDV F13540BP FLOOD 135W/4000K PHTC BK IP65, Wattage (W) 135, Lumens (lm) 15000, Efficacy (Lm/W) 110
2752635	LDV F18040B FLOODLIGHT 180W/4000K BK IP65, Wattage (W) 180, Lumens (lm) 20000, Efficacy (Lm/W) 110
2752639	LDV F18040BP FLOOD 180W/4000K PHTC BK IP65, Wattage (W) 180, Lumens (lm) 20000, Efficacy (Lm/W) 110
2752630	LEDVANCE FLOODLIGHT 20W 4000K BLACK IP65
2752631	LEDVANCE FLOODLIGHT 50W 4000K BLACK IP65

1891 RODIO LED - SIMMETRICO DIFFONDENTE



Product Codes	Description
2562688	414786-00 LED white 112W, 17100lm @ 530mA-4000K-CRI 80
2562689	414787-00 LED white 156W 21200lm @ 700mA-4000K-CRI 80

1715 CRIPTO COB MEDIUM - WIDE BEAM

Disano presents Cripto, a spotlight designed to be a possible retrofit solution for more classic models. The excellent performance of this spotlight in terms of energy savings and luminous efficiency combine with a long life of 50000 hours and materials with IP66 protection for outdoor installation. Its advanced technology and functional design are conceived to reduce consumptions and fulfil the increasing need to replace obsolete fixtures and meet the growing attention towards energy savings.

HOUSING: in die-cast aluminium with cooling fins.

DIFFUSER: tempered glass, 4 mm thick, resistant to thermal shock and impacts.

REFLECTOR: in pre-anodised aluminium

Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, IP66IK08 degree of protection according to EN 60529 standards.

These products can be installed on normally inflammable surfaces.

LED: Latest generation LED COB technology Ta-20 +40°C.

Photobiological safety class: exempt group EN62471 Power factor: ≥ 0.9


Luminous flux maintenance 80%: 50000h (L80B20)

Wind surface: L:205cm² F:855cm² .



Product Codes	Description
2562661	1715 413064-00 CRIPTO LED 10000 LM

BEGHELLI FH FLOODS



• Dimensions (mm) •			Weight max kg
L	B	H	
323	319	116	4



Product Codes	Description
2092608	FH400ED 202W (400W EQV) PRO FLOOD SYM/ASYM 25800LM - 4K
2092607	FH300ED 151W (300W EQV) PRO FLOOD SYM/ASYM 19350LM - 4K
2092606	FH200ED 101W (200W EQV) PRO FLOOD SYM/ASYM 12900LM - 4K

IP65 X-SEF LED FLOODLIGHT


5YR
WARRANTY

Product Codes	Description
2752694	8740 10W 900LM-DARK GREY-4K
2752695	8741 20W 1900LM-DARK GREY-4K
2752696	8742 30W 2650LM-DARK GREY-4K
2752697	8743 50W 4500LM-DARK GREY-4K

IP65 X-SEF LED FLOODLIGHT C/W PIR


5YR
WARRANTY

Product Codes	Description
2752698	8740S 10W C/W PIR 900LM-DARK GREY 4K
2752699	8741S 20W C/W PIR 1900LM-DARK GREY 4K
2752700	8742S 30W C/W PIR 2650LM-DARK GREY 4K
2752701	8743S 50W C/W PIR 4500LM-DARK GREY 4K

EMERGENCY

Lighting



DALTON LITHIUM

Applications


- Corridors
- Escape routes

Construction

- Aluminium body
- Polycarbonate LED tray
- Lithium (LiFePO4) battery cells

Technical Details

- 3W, 200 lm
- 3 hours non-maintained
- 3.7V 2.6Ah Lithium battery
- Circular light distribution
- Momentary manual test button fitted
- Choice of two lenses: WIDE, giving a circular distribution, OVAL, giving an oval light distribution



Product Codes	Description
2704411	NDT3/OVAL/NM3 3W Recessed Oval Distribution
2704413	NDT3/WIDE/NM3 3W Recessed Wide Distribution

PRODUCT DATASHEET

EM DL DN120 MT 3H ANTIPANIC

EMERGENCY DOWNLIGHT DN120 MANUAL TEST | Emergency Downlights with manual test function



Areas of application

- Emergency illumination of escape routes
- Antipanic lighting
- Buildings requiring up to 3 h emergency light operation

Electrical Data

Nominal wattage: 4.00 W

Photometrical Data

Color temperature: 6500 K
 Luminous flux in maintained operation mode: 235 lm
 Diameter: 140.0 mm
 Height: 48.5 mm
 Product weight: 460.00 g
 Mounting diameter: 120.0 mm
 Mounting type: Surface/Recessed



SENECA SURFACE

Dedicated LED emergency fittings for surface mounting

Applications

- Corridors
- Escape routes

Construction

- Moulded polycarbonate body construction
- Acrylic lens
- NiCd battery pack (not suitable for use below 0oC)

Technical Details

- 2W Oval - 135 lumens
- 2W Wide - 140 lumens
- Non-maintained operation
- Choice of two lenses for different light distributions:
 - Wide, giving a circular distribution
 - Oval, giving an oval light distribution.
- Momentary manual test button fitted
- Self-test version, compliant with BS5266 available. Suffix STM3 as listed




5YR
WARRANTY

Product Codes	Description
2704408	NSC2/LED/SURF/NM3 SENECA SURFACE OPEN PLAN LED NON MAINTAINED
2704409	NSC2/LED/SURF/OVAL/NM3 SENECA ESCAPE ROUTE SURFACE LED NON MAINTAINED

EVOLUX LED

- 3 watt LED.
- Lamp colour - 5000K.
- Suitable for a 35mm ceiling cut out.
- Suitable for 165mm ceiling void.
- Lamp head dimensions - diameter 45mm
- Charger dimension 195mm L x 31mm diameter
- Battery dimension 148mm L x 31mm diameter
- Supplied complete with LED lamp source
- IP20 as standard.
- Supplied with LED lamp.
- 75 lumens in emergency.




2YR
WARRANTY

Product Codes	Description
2054405	EVONM3/LED 3W NON-MAINTAINED HALO WHITE

Beacon LED Emergency Adjustable Downlight NonMaintained 5W

LED Non-Maintained adjustable die-cast aluminium downlight. 3 hour emergency output. Power and green charge LED are discreetly incorporated within the head. 120degrees beam angle.





Product Codes	Description
2734401	ABLED/3NM BEACON 5W RECESSED EMERGENCY LED, WHITE TRIM

NEBRASKA LITHIUM

IP65 LED slim emergency bulkhead with a range of attachments

5 YR
WARRANTY

IP
65



Product Codes	Description
2704216	Nebraska V3 2W LED IP65 Maint. 3Hr Lithium
SPECIAL ORDER	Nebraska V3 Recessed Mounting Kit

ASWTLED/3M SWIFT

- Small and unobtrusive LED bulkhead.
- Supplied with self-adhesive legend.
- Optic design provides optimum performance for escape route lighting. Side and rear cable entries.
- Screwless gear tray for ease of installation.
- Viewing distance 17 metres.



Product Codes	Description
2735015	ASWTLED/3M SWIFT LED 3M/NM BULKHEAD/LEGEND



GUARDIAN LED BULKHEAD 3W LED

Ultra-slim profile LED polycarbonate bulkhead, Supplied with self-adhesive legend, Side and rear cable entry, 16mm conduit entry positions, Hinged screwless gear tray for ease of installation, Viewing distance 18 Metres, 50,000 hours average life



Product Codes	Description
2735012	AGLED/3M GUARDIAN LED BULKHEAD
2735014	AGLED/KIT RECESSING KIT FOR GUARDIAN



EAGLE 3-LN-1 LED EXIT SIGN 2.5W LED WHITE

Modern slim 3-In-1 LED Exit Sign, One fitting that enables choice of three different mounting options suspension recessed or side arm wall mounting, Viewing distance 25 Metres



Product Codes	Description
2734101	AE3LED/3M/W ANSELL EAGLE 3-IN-1 LED EXIT SIGN.

ARLINGTON

Versatile LED exit sign with drop blade with multitude of fixing options, for

Applications

- Corridors
- Exits
- Escape routes

Options

- LEGENDS Alternative legends available as listed - to be ordered as separate items. For "man running through door", use suffix V2, as listed.
- FIXING ATTACHMENTS Optional fixing attachments to allow:
 - Recessed fixing
 - Wire Suspension
 - Side wall mounting
- SELF-TEST option available (suffix ST) giving built in self test regime of monthly




PLEASE NOTE THAT:

Because the frequency of charge & discharge is beyond NVC's control, batteries are excluded from the 5 year warranty on this product - NiCd cells will not perform well below 0°C

Product Codes	Description
2704112	NAL2/WH/M3 ARLINGTON 2W LED EM BLADE EXIT V2 LEGEND
SPE-LIGHTING	NAL/RMK Recessed Mounting Kit for Arlington
SPE-LIGHTING	NAL/WSK Suspension Kit for Arlington

LEXINGTON


LED 3 hour maintained/
non-maintained exit box



Product Codes	Description
2704109	NLE/3/LED/M3 LED EXIT BOX 3W MAINT. V2
2704330	NLE/LE/UP LEXINGTON V2 LEGEND UP
2704331	NLE/LE/LEFT LEXINGTON V2 LEGEND LEFT
2704332	NLE/LE/RIGHT LEXINGTON V2 LEGEND RIGHT

WATCHMAN LED EXIT SIGN MAINTAINED/ NON-MAINTAINED 3W WHITE

Modern slim 3-In-1 LED Exit Sign, One fitting that enables choice of three different mounting options suspension recessed or side arm wall mounting, Viewing distance 25 Metres



Product Codes	Description
2734100	AWLED/3M WATCHMAN LED 3M/NM WHI EXIT BOX/LEGEND

KANSAS IP65

Twinspot LED IP65 with Self Test

Applications


- Suitable for general industrial use, 0°C - +40°C

Construction

- Injection moulded ABS body
- Polycarbonate heads, including lens
- NiCd cells secured with fixing straps
- Suitable for mounting in any orientation
- Heads can be rotated & tilted
- Piano key terminal block for ease of installation

Technical Details

- 3-hour Non-Maintained
- 2 x 3W body & heads for use from 0°C to 40°C
- 450 total lumen output
- Self-Testing compliant with BS5266 comprising of a monthly functional test & an annual 3-hour duration test
- LED indicators & audible buzzer to advise on any failure status and an annual 3-hour test




Product Codes	Description
2704003	NKS2X3/LED/IP65/NM3KANSAS2X3WTWINSPOTIP65

KANSAS IP20

Twinspot LED IP20 fittings

Technical Details

- 3-Hour Non-Maintained
- 2 x 3W combined body & heads for use from 0°C - +25°C
- 300 lumens total output.



Product Codes	Description
2704004	NKS2X3/IP20/NM3KANSASLEDTWINSPOTIP20X3WNM

PRESENCE DETECTOR 360° MONOBLOC DALI/DSI EE 816. DALI SENSOR

Presence detector 360° monobloc DALI/DSI

Technical Details

- Supply voltage 230 V +10% / -15%
- Protection index IP IP41
- Type of load 24 DALI/ DSI ballasts
- Detection angle 360 °
- Diameter of the floor detection area 7 m
- Maximum Mounting Height 4 m
- Brightness measurement range 5/1000 Lux
- Time delayed range 1min to 1h
- Colour white
- Sensitivity setting no
- Remote controllable EE807, EE808



Product Codes	Description
2062561	EE816 HAGER DSI/DALI DIMM. PIR 7MTR

HAGER EE815 SENSOR

Technical Details

- Supply voltage 230 V +10% / -15%
- Frequency 50/60 Hz
- Maximum Mounting Height 4 m
- Colour white
- Detection angle 360 °
- Diameter of the floor detection area 7m
- Remote controllable EE807, EE808



Product Codes	Description
2062560	EE815 HAGER PIR 7MTR NON DIMMABLE

New Hager Occupancy Sensor Range

The Hager range of occupancy sensors detect infra-red radiation and ambient light levels to provide simple and cost effective means of lighting control.

Positioning Considerations

The EE8 range of sensors should be mounted in the centre of the group of luminaires to be controlled and the optimum all round coverage is achieved with the unit mounted at a height of 2.5m. The coverage for these sensors at this height is approximately 5m diameter for small movement such as working at a desk, and 7m for larger movements such as walking.

Programming Tool

The EE807 programming tool allows the setting of time out period.

Lux level

Lux level adjustment (+ or - 100 lux steps)

Presence / Absence

Power up On / Off

Passive photocell / Active photocell

Memory settings (2)

Walk test mode

Remote Control

Also available is the EE808 remote control tool which allows lighting to be overridden On or Off with standard luminaires.

Technical Details

- Recommended Mounting Height: 2.5m
- Detection Angle & Range: 360°
- Range: Approximately 5m Small Movement
- 7m Large Movement @ 2.5M Mounting Height
- Photocell Lux Adjustment: 5 - 1000 Lux Adjustable
- Time Delay Adjustable Between: 1 Min - 1 Hour
- Power Supply: 230VAC @ 50Hz
- Current Consumption: 2.4VA / 270mW

Capacity / Loading

- Incandescent Halogen Lamp 230V: 10A Max
- Resistive Load (AC1): 16A Max
- Fluorescent Load: 4.3A Max
- Compact Fluorescent: 23 x 23W
- Operating Temperature: -10°C to +45°C
- IP Rating: IP41

Weight

- EE815: 100g
- Dimensions: 80 x 80 x 70mm
- Surface Mount Kit: EEK005
- Ceiling Void Depth Required: 70mm
- Ø of Mounting Hole: 60mm



EE807



EE808

Site Lighting



LED Non Corrosive Work Light

An LED non corrosive work light range with a operating temperature of 0°C to +50°C, ideal for use in any indoor/outdoor commercial or industrial construction sites.



Material construction

- Polycarbonate – Yellow base
- Polycarbonate - Opal diffuser



120° Beam angle







Dual brackets included for suspension and wall mounting



3 hour emergency duration option available



Kellihers Code	Model No.	Colour	Emergency	Wattage (W)	Lumens (lm)	Efficacy (Lm/W)	Colour Temperature (K)
2170001	RXL-TRLED8010	2FT WEATHERPROOF 110V YELLOW BODY		20	2000	100	6300K
2170002	RXL-TRLED8011	2FT WEATHERPROOF 110V YELLOW BODY E3	Y	20	2000	100	6300K
2170301	RXL-TRLED8020	5FT WEATHERPROOF 110V YELLOW BODY		36	3960	110	6300K
2170302	RXL-TRLED8021	5FT WEATHERPROOF 110V YELLOW BODY E3	Y	36	3960	110	6300K



LED Plasterers Light

An LED Plasterers light perfect for working in both indoor and outdoor confined spaces, with operating temperatures of 0°C to +40°C.



Material construction

- Polycarbonate - Yellow base
- Polycarbonate - Opal diffuser



120° Beam angle



Supplied with foldaway stand for ease of storage and transportation



Supplied with two 16A outlet connections for linkable applications



5m lead and 16A 110V yellow plug




Kellihers Code	Model No.	Description	Wattage (W)	Lumens (lm)	Efficacy (lm/W)	Colour Temperature (K)
2172402	RXL-P1000	2FT PLASTERERS LIGHT A-FRAME 110V	20	2200	110	6300K
2172405	RXL-P1010	2FT PLASTERERS LIGHT TRIPOD 110V	20	2200	110	6300K
2172406	RXL-P1020	5FT PLASTERERS LIGHT TRIPOD 110V	30	3300	110	6300K

IP44


1
YEAR
WARRANTY

IK08


RXL-P1000



RXL-P1010



RXL-P1020



LED Task Light

A range of task and tripod worklights perfect for indoor and outdoor illumination.



Material construction

- Aluminium body – Yellow
- Tempered glass cover



Complete with 1.5m lead and 16A plug





Kellihers Code	Model No.	Colour	Wattage (W)	Lumens (lm)	Efficacy (Lm/W)	Colour Temperature (K)
2172407	RXL-S4010	110v PORTABLE TASK LIGHT	10	900	90	4000K

IP65

3
YEAR
WARRANTY
30,000 HOURS

IK08



LED Tripod Worklight

A range of task and tripod worklights perfect for indoor and outdoor illumination.



Material construction

- Light fitting -Aluminium body - Yellow
- Tempered glass cover
- Tripod - Die cast Aluminium - Yellow



Comes with a telescopic tripod for easy storage and transportation



Complete with 3m lead and 16A plug







Kellihers Code	Model No.	Colour	Wattage (W)	Lumens (lm)	Efficacy (lm/W)	Colour Temperature (K)
2172408	RXL-S4110	110V TRIPOD TASK LIGHT	10	900	90	4000K
2172409	RXL-S4120	110V TWIN TRIPOD TASK LIGHT	10	900	90	4000K



RXL-S4110

RXL-S4120



Site Floodlight

A range of floodlights suitable for use in industrial and commercial applications such as construction sites.



Material construction

- Aluminium body – Yellow
- Toughened glass cover




500mm lead




Kellihers Code	Model No.	Colour	Wattage (W)	Lumens (lm)	Efficacy (Lm/W)	Colour Temperature (K)
2172601	RXL-N6279	110V SITE FLOODLIGHT	50	4500	90	4000K
2172602	RXL-N6280	110V SITE FLOODLIGHT	70	6300	90	4000K
2172603	RXL-N6281	110V SITE FLOODLIGHT	100	9000	90	4000K
2172604	RXL-N6282	110V SITE FLOODLIGHT	150	13500	90	4000K



RXL-N6279 / RXL-N6280 /
RXL-N6281



RXL-N6282



LED Festoon Kits

A range of festoon lighting kits that are an ideal temporary lighting solution for construction sites due to their light weight and flexibility.



22M Length with 2M Spacings



Option to have festoon only or lamp included kit comes with 10 LED lamps



Kellihers Code	Model No.	Description
2176801	RXL-SEFLEDES	110V 22M KIT INC ES LAMPS
2176802	RXL-SEFLEDBC	110V 22M KIT INC BC LAMPS



Integrated Festoon Kit



Suitable temporary lighting solution for indoor & outdoor use



Complete 20m kit with 7 fully integrated LED lamps



Kellihers Code	Model No.	Description
2176801	SEFLKITINT	20M INTEGRATED FESTOON KIT 7 X 10W



Site Accessories

A range of site accessories ideal for domestic, commercial and industrial applications.

110V Transformers



Robust GRP case with carry handle



Resettable thermal cut out



Supplied with 2M cable and 13A plug



Kellihers Code	Model No.	Colour	Intermittent Rating	Continuous Rating	Weight
4859808	RXL-15002/B	1500VA SITE TRANSFORMER	1.5KVA	0.9KVA	13
4859805	RXL-3300/2/B	3300VA SITE TRANSFORMER	3.3KVA	2.2KVA	18
4859809	RXL-10000/1PH	10000VA SITE TRANSFORMER	10KVA	7.0KVA	63



Power Splitter



Power splitter with four 16A 110V outlets



Heavy duty yellow steel case with carry handle



Complete with lead and 16A 110V plug






Kellihers Code	Model No.	Colour	Lead Length	Sockets
3450301	RXL-PS45	POWER SPLITTER WITH CABLE	2.5M	4



Site Accessories

Extension Lead Reels




-  2 x 110V 16A dust covered outlet sockets
-  Easy wind handle
-  Optimised design for increased cable capacity



Kellihers Code	Model No.	Description	Length (Metres)	Voltage (V)	Max Load Unwound	Max Load Wound
3450363	RXL-SE1010	CASSETTE CABLE REEL 16A	10	110v	1760	770
3450365	RXL-SE1030	OPEN CABLE REEL 16A	25	110v	1760	660



Extension Lead

-  Made with highly durable arctic grade cable
-  Fitted with 16A 110v plug and coupler
-  Must be used uncoiled



Kellihers Code	Model No.	Description	Length (Metres)	Max Load Unwound	Max Load Wound	H Frame
3450302	RXL-SE3010	YELLOW 1.5MM 16A EXT LEAD	14	1760	770	
3450303	RXL-SE3030	YELLOW 2.5MM 16A EXT LEAD	14	1760	770	
3450310	RXL-SE3050	YELLOW 1.5MM 16A EXT LEAD	25	1760	770	Y
3450311	RXL-SE3070	YELLOW 2.5MM 16A EXT LEAD	25	1760	770	Y



22 BRANCHES ACROSS IRELAND

Kellihers Electrical **BALLYMOUNT**

M50 Business Park,
Ballymount Rd Upper,
Dublin 12
01 4566717

Kellihers Electrical **FINGLAS**

Unit 27, North Park,
North Road, Finglas,
Dublin 11
01 8041160

Kellihers Electrical **DUNDALK**

Ard Easmuinn Road,
Dundalk,
Louth
042 9327854

Kellihers Electrical **CORK- TRAMORE ROAD**

Tramore Road,
Cork
021 4704100

Kellihers Electrical **LIMERICK**

Dock Road,
Limerick
061 417442

CT Electric **SLIGO**

Finisklin Industrial
Estate,
Sligo
071 9145068

Kellihers Electrical **SANDYFORD**

Unit E3, Three Rock Rd,
Sandyford Industrial
Estate, Dublin 18
01 2952011

Kellihers Electrical **BRAY**

Unit A3,
Old Court Industrial Est.
Boghall Road
Bray, Co.Wicklow
01 204 2670

Kellihers Electrical **NAAS**

Unit A1, Toughers
Industrial Estate,
Newhall, Naas, Kildare
045 447860

Kellihers Electrical **KILKENNY**

Unit 11A, Loughboy
Industrial Estate,
Kilkenny
056 7750410

Kellihers Electrical **CORK- EASTGATE**

Units 31-32 East Gate
Drive, Eastgate,
Little Island, Cork
021 4296240

Kellihers Electrical **ENNIS**

Unit 9 Quinn Road
Business Park, Ennis,
Clare
065 6844233

CT Electric **ATHLONE**

Unit 3 Daneswell
Business Park,
Monksland, Athlone
090 6494681

Kellihers Electrical **CROKE PARK**

Unit G2 Croke Park
Industrial Estate,
Russell Street, Dublin 1
01 8554704

Kellihers Electrical **PORTLAOISE**

Clonminam Industrial
Estate, Portlaoise,
Laois
057 8664660

Kellihers Electrical **WATERFORD**

Tramore Road,
Waterford
051 377755

Kellihers Electrical **CORK- MALLOW ROAD**

North Point Business
Park, Mallow Road,
Cork
021 4932300

CT Electric **GALWAY**

Sean Mulvoy Road,
Galway
091 745300

Kellihers Electrical **TRALEE**

Ballymullen,
Tralee,
Kerry
066 7145300

CT Electric **CASTLEBAR**

Castlebar Industrial
Estate, Castlebar,
Mayo
094 9023650

Kellihers Electrical **KILLARNEY**

Ross Road,
Killarney,
Kerry
064 6633985

CT Electric **BALLINA**

Unit 7 Moyvalley
Business Park,
Ballina, Mayo
096 60420

