

LED PANEL RANGE

2751401 2751402 2751403 2751405



Kellihers Electrical
REXEL GROUP



LED Recessed Panel

APPLICATIONS

- Versatile fitting which is suitable for a wide range of applications such as offices, shops, reception areas, restaurants, hotels, schools & hospitals

SPECIFICATION


- LED alternative for T8 LED fluorescent lay-in modular fittings
- Fits into standard size ceiling grid of 15mm to 24mm
- Emergency options available
- Suitable for switching by PIR, Microwave sensor or photocell
- Accessories available for suspension or surface mounted applications

TECHNICAL DETAILS


- Efficacy- 90 lm/cw to 108 lm/cw
- CRI 80
- IP20 Rating
- CCT 4000K- 2751401, 2751403 & 2751405
- CCT 5000K- 2751402




Length: 1,195
Width: 295
Depth: 10



Length: 1,195
Width: 595
Depth: 12



Length: 595
Width: 595
Depth: 10



Code	Description	Wattage (W)	Warranty (yrs)	Lifetime (hrs)	Lumens (lm)	Efficacy (lm/W)	Colour Temp (K)	CRI	Beam Angle
2751401	600 X 600 LED Panel	40W	5	50,000	3600	90	4,000	80	110
2751402	600 X 600 LED Panel	40W	5	50,000	3700	90.5	5,000	80	110
2751403	1200 x 300 LED Panel	40W	5	50,000	3600	90	4,000	80	110
2751405	1200 x 600 LED Panel	60W	5	50,000	6500	108	4,000	80	120