

Globe LED

SUSPENDED LUMINAIRES



CE UK

LED

IP20

IK01

BIM



Description

The light-weight appearance of the Globe LED makes it the perfect fitting for high ceiling rooms such as receptions and lobbies where suspended fittings are required.

Application

- Double Height Areas
- Receptions
- Atriums



Body & Finish

Steel body with a matt finish and a glass sphere diffuser.

Attachments



Order Codes

Wattage	Luminous Flux	lm/W	Diameter	Depth	Product Code
13.0 W	1033 lm	79 lm/W	315 mm	315 mm	SGL/LED/1520/GLB/PDT
18.0 W	1360 lm	76 lm/W	315 mm	315 mm	SGL/LED/2000/GLB/PDT
20.0 W	1666 lm	83 lm/W	315 mm	315 mm	SGL/LED/2450/GLB/PDT
23.0 W	2040 lm	89 lm/W	315 mm	315 mm	SGL/LED/3000/GLB/PDT

Additional lumen outputs are available due to mA ratings and codes may vary from those stated. Please contact us for further details.

Sizes

- Diameter: 315 mm
- Depth: 315 mm

Control Gear

OSRAM

- Standard LED
- Dimmable LED

Code Options

Main Attributes

- 50,000h L80 at 25°C
- Self Cooling
- Colour Rendering Index >80
- 7 Year Guarantee*
- CE Marked

* Please refer to the Warranty for more information.

LED Boards

- OSRAM LED ES
- Colour Temperatures Available: 3000k/4000k/5000k
- All LED data and performance data is taken at an ambient temperature of +25°C

Photometrics

-